

PRODUCTLIST MAGONAREZ S.L

WWW.MAGONAREZ.COM

POLYURETHANE DISPERSIONS

Productname	Solids % +/-1%	pH	Viscosity* m.Pas	% DMM	Tg °C	Properties
MAGONA-PUR AQUA 1810-A	50	7,0 - 8,0	< 500	0	< 0	PU- elastomer in water for topcoats for flooring, screeds, parkingdecks. Topcoats for exterior, elastic weather resistant coatings. High tensile strength, excellent elongation (> 900 %) 900% elongation stress 5,8 MPa
MAGONA-PUR AQUA 1815-A	45	7,0 - 8,0	< 500	1,0	< 0	PU- elastomer in water for highly resilient coatings, for sportsfloors, domestic- and industrial wooden floors and parking decks.
MAGONA-PUR AQUA 1820-A	45	7,0- 8,0	< 500	2,0	2	General purpose PU-elastomer for quality topcoats. Elongation > 500 %
MAGONA-PUR AQUA 1830	45	7,0 - 8,0	< 500	4,5	< 0	Topquality, PU-elastomer in water for sealants, Jointfillers, Screeds and Flooringsystems

* Brookfield RVE / Spindle 2 / 50 rpm / 20° C

www.magonarez.com

January 2015

Note : Typical values, no specifications